

UNITED STATES PATENT APPLICATION FOR:

**LOW K DIELECTRIC COMPOSITE LAYER FOR INTEGRATED CIRCUIT
STRUCTURE WHICH PROVIDES VOID-FREE LOW K DIELECTRIC
MATERIAL BETWEEN METAL LINES WHILE MITIGATING VIA POISONING**

By: **Wilbur G. Catabay**
13199 McDole Street
Saratoga, CA 95070

Citizenship: U.S.A.

Richard Schinella
12206 Vista Arroyo Court
Saratoga, CA 95070

Citizenship: U.S.A.

Certification Under 37 CFR 1.10

I hereby certify that these documents referred to as enclosed herein are being deposited with the United States Postal Service on this date March 15, 2002 in an envelope as "Express Mail Post Office to Addressee" Mailing Label Number ET662218667US addressed to: Assistant Commissioner for, Washington, D.C. 20231.

John P. Taylor
Person Mailing Paper

John P. Taylor
Signature of Person Mailing Paper

-1-

LOW K DIELECTRIC COMPOSITE LAYER FOR INTEGRATED CIRCUIT
STRUCTURE WHICH PROVIDES VOID-FREE LOW K DIELECTRIC MATERIAL
BETWEEN METAL LINES WHILE MITIGATING VIA POISONING



BACKGROUND OF THE INVENTION

5 1. Field of the Invention

This invention relates to integrated circuit structures. More particularly, this invention relates to the formation of a composite low k dielectric layer over and between metal lines of an integrated circuit structure.

10 2. Description of the Related Art

In the continuing reduction of scale in integrated circuit structures, both the width of metal interconnects or lines and the horizontal spacing between such metal lines on any particular level of such interconnects have become smaller and smaller. As a result, horizontal capacitance has increased between such conductive elements. This increase in capacitance, together with the vertical capacitance which exists between metal lines on different layers, results in loss of speed and increased cross-talk. As a result, reduction of such capacitance, particularly horizontal capacitance, has received much attention. One proposed approach to solving this problem of high capacitance is to replace the conventional silicon oxide (SiO_2) dielectric material, having a dielectric constant (k) of about 4.0, with another dielectric material having a lower dielectric constant to thereby lower the capacitance.

20 In an article by L. Peters, entitled "Pursuing the Perfect Low-K Dielectric", published in Semiconductor International, Volume 21, No. 10, September 1998, at pages 64-74, a number of such alternate dielectric materials are disclosed and discussed. Included in these dielectric materials is a description of a low k dielectric material having a dielectric constant of about 3.0 formed using a chemical vapor deposition (CVD) process developed by Trikon
25 Technologies of Newport, Gwent, U.K. The Trikon process is said to react methyl silane ($\text{CH}_3\text{-SiH}_3$) with hydrogen peroxide (H_2O_2) to form monosilicic acid which condenses on a cool wafer and is converted into an amorphous methyl-doped silicon oxide which is annealed at 400°C to remove moisture. The article goes on to state that beyond methyl silane, studies

show a possible k of 2.75 using dimethyl silane in the Trikon process. The Peters article further states that in high density plasma CVD (HDP-CVD), dielectric material formed from methyl silane or dimethyl silane and O₂ can provide a k as low as 2.75; and that trimethyl silane, available from Dow-Corning, can be used to deposit low-k (2.6) dielectric films.

- 5 The use of this type of low k material has been found to result in the formation of void-free filling of the high aspect ratio space between parallel closely spaced apart metal lines with dielectric material having a lower dielectric constant than that of convention silicon oxide, thereby resulting in a substantial lowering of the horizontal capacitance between such adjacent metal lines on the same metal wiring level.

However, the substitution of such low k dielectric materials for conventional silicon oxide insulation has not been without its own problems. Formation of the low k carbon doped dielectric material by the Trikon process is much slower than the conventional formation of undoped silicon oxide dielectric material. For example, in the time it takes to form a layer of low k dielectric material by the Trikon process on a single wafer, it may be possible to deposit a conventional dielectric layer of the same thickness on as many as 5 wafers.

However, even more importantly, it has been found that the subsequent formation of vias, or contact openings, through such low k dielectric material to the underlying conductive portions such as metal lines, or contacts on an active device, can contribute to a phenomena known as via poisoning wherein filler material subsequently deposited in the via, such as a titanium nitride liner and tungsten filler material, fails to adhere to the via surfaces. Apparently the presence of carbon in the low k dielectric material formed by the Trikon process renders the material more susceptible to damage during subsequent processing of the structure. For example, contact openings or vias are usually etched in the dielectric layer through a resist mask. When the resist mask is subsequently removed by an ashing process, damage can occur to the newly formed via surfaces of the low k material resulting in such via poisoning.

As mentioned above in the Peters article, high density plasma (HDP) has also been used to form void-free low k dielectric material. In this process, a high density plasma is used with methyl silane or dimethyl silane and O₂ to form a low k silicon oxide dielectric layer having

a dielectric constant said to be as low as 2.75. However, the deposition rate of HDP low k dielectric material is similar to that of the Trikon process, making it also not economically attractive for the formation of a layer of low k dielectric material.

5 It has also been proposed to deposit low k silicon oxide dielectric material by other processes such as by plasma enhanced chemical vapor deposition (PECVD), using CH_4 and/or C_4F_8 and/or silicon tetrafluoride (SiF_4) with a mixture of silane, O_2 , and argon gases. Plasma enhanced chemical vapor deposition is described more fully by Wolf and Tauber in "Silicon Processing for the VLSI Era", Volume 1-Process Technology (1986), at pages 171-174.

10 While the formation of a low k silicon oxide dielectric material by PECVD is much faster than the formation of the same thickness low k silicon oxide dielectric layer by the Trikon or HDP-CVD processes (i.e., at rates approaching the deposition rate of conventional silicon oxide), low k silicon oxide dielectric material deposited by PECVD has poor filling characteristics in high aspect ratio regions, resulting in the formation of voids in the dielectric materials deposited by PECVD in the spaces between the closely spaced apart metal lines in such structures.

15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945
9950
9955
9960
9965
9970
9975
9980
9985
9990
9995
10000
10005
10010
10015
10020
10025
10030
10035
10040
10045
10050
10055
10060
10065
100

OXYNITRIDE CAPS OVER CLOSELY SPACED APART METAL LINES" was also filed by one of us with others on the same date as this application and is assigned to the same assignee as this application. The subject matter of Docket No. 99-060 is also hereby incorporated by reference. In that application, a layer of silicon oxynitride (SiON) is formed over the top surface of the metal lines to serve as an anti-reflective coating (ARC), a hard mask for the formation of the metal lines, and a buffer layer for chemical mechanical polishing (CMP). Low k silicon oxide dielectric material having a high carbon doping level is then formed in the high aspect regions between closely spaced apart metal lines up to the level of the silicon oxynitride. CMP is then applied to planarize the upper surface of the low k carbon-doped silicon oxide dielectric layer, using the SiON layer as an etch stop, i.e., to bring the level of the void-free low k silicon oxide dielectric layer even with the top of the SiON layer. A conventional (non-low k) layer of silicon oxide dielectric material is then deposited by plasma enhanced chemical vapor deposition (PECVD) over the low k layer and the SiON layer. A via is then cut through the second dielectric layer and the SiON to the top of the metal line. Since the via never contacts the low k layer between the metal lines, via poisoning due to exposure of the low k layer by the via does not occur.

It would, however, be highly desirable to provide a structure having a low k dielectric layer, and process for making same, wherein a composite layer of low k dielectric material can be formed having void-free filling characteristics for high aspect ratio regions between closely spaced apart metal lines while mitigating the poisoning of vias subsequently formed in the low k dielectric material and with less reduction of throughput in the deposition apparatus, using a process wherein all steps used to form such a composite layer could be carried out in the same vacuum processing apparatus. That is, the deposition steps could be carried out, for example, in multiple stations or multiple chambers in the same vacuum apparatus, to decrease contamination of the deposited materials as well as to improve the processing economics, including equipment investment and required space.

SUMMARY OF THE INVENTION

In accordance with the invention, a composite layer of low k silicon oxide dielectric material is formed on an oxide layer of an integrated circuit structure on a semiconductor substrate having closely spaced apart metal lines. The composite layer of low k silicon oxide dielectric

material exhibits void-free deposition properties in high aspect ratio regions between the closely spaced apart metal lines, deposition rates in other regions comparable to standard k silicon oxide, and reduced via poisoning characteristics. The composite layer of low k silicon oxide dielectric material is formed by depositing, over the oxide layer and in high aspect ratio regions between the closely spaced apart metal lines, a first layer of low k silicon oxide dielectric material exhibiting void-free deposition properties until the resulting deposition of low k silicon oxide dielectric material reaches the level of the top of the metal lines on the oxide layer. A second layer of low k silicon oxide dielectric material, having a faster deposition rate than the first layer, is then deposited over the first layer up to the desired overall thickness of the low k silicon oxide dielectric layer. In a preferred embodiment, the steps to form the resulting composite layer of low k silicon oxide dielectric material are all carried out in a single vacuum processing apparatus without removal of the substrate from the vacuum apparatus.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a fragmentary vertical cross-sectional view of an integrated circuit structure having an oxide layer formed thereon with metal lines formed over the oxide layer.

Figure 2 is a fragmentary vertical cross-sectional view of the structure of Figure 1 after having a base layer of dielectric material deposited over the metal lines and oxide layer.

Figure 3 is a fragmentary vertical cross-sectional view of the structure of Figure 2 after deposition of a first layer of low k dielectric material up to the height of the metal lines.

Figure 4 is a fragmentary vertical cross-sectional view of the structure of Figure 3 after deposition of a second layer of low k dielectric material over the first layer of low k dielectric material, and further showing a via cut through the second dielectric layer down to the top of one of the metal lines.

Figure 5 is a top section view of a multiple chamber vacuum apparatus useful in the practice of the invention.

Figure 6 is a fragmentary vertical cross-sectional view of the structure of Figure 3 after a chemical mechanical polishing (CMP) of the first layer of low k dielectric material deposited over the metal lines and oxide layer in accordance with a second embodiment of the invention.

Figure 7 is a fragmentary vertical cross-sectional view of the structure of Figure 6 after deposition of a second layer of low k dielectric material over the polished first layer of low k dielectric material, and further showing a via cut through the second dielectric layer down to the top of one of the metal lines.

Figure 8 is a flowsheet illustrating the process of the invention.

DETAILED DESCRIPTION OF THE INVENTION

The invention, in its broadest form, comprises a composite layer of low k silicon oxide dielectric material formed on an oxide layer of an integrated circuit structure wherein the composite layer exhibits void-free deposition properties in high aspect ratio regions between closely spaced apart metal lines, deposition rates in other regions comparable to standard k silicon oxide, and reduced via poisoning characteristics. The composite layer of low k silicon oxide dielectric material is formed by depositing over the oxide layer and the metal lines a first layer of a low k silicon oxide dielectric material exhibiting void-free deposition properties in high aspect ratio regions between closely spaced apart metal lines until the resulting deposition of low k silicon oxide dielectric material reaches the level of the top of the metal lines on the oxide layer. A second layer of low k silicon oxide dielectric material, having a faster deposition rate than the first dielectric layer, is then deposited over the first layer up to the desired overall thickness of the low k silicon oxide dielectric layer.

The term "low k", as used herein, is intended to define a dielectric constant of a dielectric material of 3.5 or less. Preferably, the dielectric constant of a "low k" material will be 3.0 or less.

The term "void-free", as used herein to describe the absence of voids in the first layer of low k dielectric material formed in the high aspect region between the metal lines, is intended to

define a material have no voids therein discernable in cross-sections using scanning electron microscopy (SEM).

Referring now to Figures 1-4, the preferred process of the invention will be described. Figure 1 shows a previously formed integrated circuit structure 2 formed on and in a semiconductor substrate (not shown) with an insulation layer 10, such as an oxide layer (e.g., silicon oxide), formed over integrated circuit structure 2. Insulation layer 10 may be formed over an underlying layer of metal interconnects (metal lines) forming a part of integrated circuit structure 2, or oxide layer 10 may be formed directly over devices such as, for example, MOS transistors, formed in the semiconductor substrate. Several parallel and closely spaced apart metal lines 14a-14c are shown formed over insulation layer 10. Metal lines 14a-14c normally will comprise a stack of conductive layers of metals and metal compounds such as, for example, a stack containing a titanium bottom layer, a titanium nitride layer, an aluminum (or aluminum/copper) main layer, and a titanium nitride capping layer, wherein each layer serves a specific purpose and the stack collectively functions to electrically connect one portion of the integrated circuit structure with another portion. By way of example, metal line 14a is shown in Figure 1 connected to the underlying integrated circuit structure 2 by a via or contact opening 18 filled with a conductive material such as tungsten.

In Figure 2, metal lines 14a-14c and insulation layer 10 are shown covered with a thin conformal barrier layer 20 of insulation such as a thin layer of conventional (standard k) silicon oxide deposited by plasma enhanced chemical vapor deposition (PECVD). Barrier layer 20 serves to isolate the first low k dielectric layer to be applied over barrier layer 20 from underlying oxide layer 18 and metal lines 14a-14c. Base layer will range in thickness from a minimum thickness of about 50 nanometers (nm) which is sufficient to provide the desired metallurgical separation up to a maximum thickness of about 500 nm. Barrier layer 20 may be thicker, but it will be appreciated that since barrier layer 20 does not comprises low dielectric material, the use of thicknesses greater than the minimum needed to separate oxide layer 18 and metal lines 14a-14c from the first low k dielectric layer will have an adverse effect on the overall capacitance of the structure.

After deposition of barrier layer 20 over metal lines 14a-14c and oxide layer 18, the first layer 24 of low k silicon oxide dielectric material is deposited over the structure to form void-free low k dielectric material 24a and 24b respectively in the high aspect regions between closely spaced apart metal lines 14a-14c. The low k dielectric material and process used to fill these regions must be capable of forming void-free dielectric material having a dielectric constant of 3 or less in openings having a high aspect ratio of at least 2.5.

Such void-free low k silicon oxide dielectric material may be deposited by reacting hydrogen peroxide with a carbon-substituted silane such as methyl silane, as described in Dobson U.S. Patent No. 5,874,367, the subject matter of which is hereby incorporated by reference. The void-free low k silicon oxide dielectric material may also be deposited by reacting a mild oxidant such as hydrogen peroxide with the carbon-substituted silane materials disclosed in Aronowitz et al. Serial No. 09/274,457, filed on March 22, 1999, and assigned to the assignee of this application, the subject matter of which is also hereby incorporated by reference.

Alternatively, the void-free low k dielectric material may be formed by using a high density plasma (HDP-CVD) process wherein oxygen (O_2) is reacted with either a mixture of silane and argon and a carbon-substituted silane, or a mixture of silane and argon and a fluorinated silane. High density plasma chemical vapor deposition (HDP-CVD) superimposes a plasma deposition process carried out at low frequency power, e.g., 400 kHz, and a sputter etching process carried out at high frequency, e.g., 13.56 MHz to provide a void-free deposition.

Any other deposition process capable of forming void-free low k silicon oxide dielectric material in the high aspect ratio regions between closely spaced apart metal lines can be substituted for the above-described processes.

Regardless of which process is used, in accordance with the invention, the void-free low k silicon oxide dielectric material is deposited until layer 24 of low k silicon oxide dielectric material reaches the height of metal lines 14a-14c. At this point the deposition process is halted. This end point may be empirically determined. Failure to deposit sufficient low k dielectric material to reach the top of metal lines 14a-14c may have a negative impact on either the absence of voids in the dielectric material or the capacitance developed horizontally

between adjacent metal lines. On the other hand, an excessive amount of void-free low k silicon oxide dielectric material deposited above the height of metal lines 14a-14c could have an adverse effect with regard to via poisoning, as well as lowering the overall throughput time for forming the structure. As shown in Figure 3, at 24c-24e, deposition of a slight excess of void-free low k dielectric material over the tops of metal lines 14a-14c, however, may be unavoidable. Generally, the height of the deposited void-free low k dielectric layer should be about ± 50 nm of the height of the metal lines.

Turning now to Figure 4, a second layer 30 of low k dielectric material is now deposited over the entire structure up to the desired thickness of the composite dielectric layer. This second layer of low k dielectric material will comprise a low k dielectric material capable of being deposited at a rate at least faster than the rate of deposition of the first layer, and preferably at a deposition rate comparable to the rate of deposition of conventional (non-low k) dielectric materials. For example, a low k carbon and/or fluorine-doped silicon oxide dielectric layer may be formed by adding CH_4 and/or C_4F_8 and/or silicon tetrafluoride (SiF_4) as additives or dopants to a mixture of silane, O_2 , and argon gases in a PECVD process to deposit a low k silicon oxide dielectric layer at deposition rates comparable to non-low k dielectric materials.

The total thickness of second dielectric layer 30 will depend on the desired total thickness of low k dielectric material in the composite layer (low k dielectric layer 24 and low k dielectric layer 30). Many semiconductor dielectric applications require that a thick dielectric film of about 1.8 micrometers (μm) be initially formed and then polished back by CMP to about 700 nm (7 kÅ) to provide the required smooth surface for the next layer of metal lines. Thus, when the height of metal lines 14a-14c (and, therefore, the height of first low k layer 24 of dielectric material) is 560 nm (5.6 kÅ) and the total desired height of the composite low k dielectric layer comprising layer 24 and layer 30 is 1800 nm (18 kÅ), the height or thickness of second low k dielectric layer 30 will be about 1240 nm (12.4 kÅ). Usually the total thickness of the composite low k dielectric layer will range from about 1600 nm (16 kÅ) to about 3000 nm (30 kÅ), the height of the metal lines will range from about 500 nm (5 kÅ) to about 1200 nm (12 kÅ), and the thickness of second low k dielectric layer 30 will range from about 1000 nm (10 kÅ) to about 2400 nm (24 kÅ).

After formation of second low k silicon oxide dielectric layer 30, vias are cut through second layer 30 down to the underlying metal lines, such as filled via 34 shown in Figure 4 cut through layer 30 down to metal line 14b. It will be noted that when the height of first low k dielectric layer 24 is slightly above the height of metal lines 14a-14c, vias such as via 34 cut through second low k dielectric layer 30 will pass through the portion (e.g., 24c-24e) of first low k dielectric layer 24 which is above metal lines 14a-14c. If this portion of low k dielectric layer 24 above metal lines 14a-14c is thin, i.e., less than 100 nm (1000 Å), any adverse via poisoning effects attributable to exposure of this portion of first low k dielectric layer 24 by formation of the via should be minimal.

In the preferred embodiment just discussed and illustrated in Figures 1-4, the steps to form the resulting composite layer of low k silicon oxide dielectric material may all be carried out in a single vacuum processing apparatus having multiple stations or multiple vacuum chambers. This permits the entire process of forming the composite low k dielectric layer to be carried out without removal of the wafer from the vacuum apparatus. This provides advantages in process economics, since throughput can be increased and only a single vacuum apparatus is used, thus providing savings in equipment investment and floor space. Also, by performing all of the steps in a single vacuum apparatus, exposure to atmospheric contamination is reduced, thus minimizing impact the effects of such atmospheric contamination on film properties and particle contamination.

Figure 5 illustrates a typical commercially available multiple chamber vacuum apparatus such as the Endura multiple chamber vacuum apparatus available from Applied Materials, Inc. which may be used when the steps of the process are carried out in a single vacuum apparatus. The vacuum processing apparatus, the central portion of which is generally indicated at 40, is maintained under vacuum by a vacuum pump 110 through a port 100. A semiconductor substrate, already having the metal lines formed over an oxide layer, is introduced into the vacuum apparatus through a first load lock 50. A robot arm 54 in a central vacuum chamber 60 moves the semiconductor substrate from load lock 50 through central chamber 60 into a first vacuum processing chamber 62 through a slit valve 64. First vacuum processing chamber 62 could be used, for example, to deposit base dielectric layer 20 over the metal lines and oxide layer on the substrate by PECVD. After deposition of barrier layer 20, slit valve 64 is

then opened and robot arm 54 removes the coated substrate back to central vacuum chamber 60. A slit valve 74 on a second vacuum processing chamber 72 is then opened and the substrate is placed in the second processing chamber by robot arm 54. In this chamber, void-free low k dielectric material is deposited to fill the spaces between the closely spaced apart metal lines.

Since this particular deposition step requires more processing time, the next vacuum processing chamber 82 may also be used to deposit the void-free low k material between the metal lines, i.e., chambers 72 and 82 could be used as parallel processing chambers to process two different substrates at the same time - or preferably at staggered but overlapping times. Robot arm 54 then removes the substrate from either chamber 72 through slit valve 74, or from chamber 82 through slit valve 84, and inserts it into vacuum processing chamber 92 through slit valve 94. The second layer of low k dielectric material is then be deposited, e.g., by PECVD, on the substrate over the metal lines, and over the void-free first layer of low k dielectric material between the metal lines until the desired thickness of the composite layer is reached. This substrate is then removed from chamber 92 and may then be removed from the vacuum apparatus for further processing which may, for example, comprise a CMP step in preparation for the formation of vias through the composite layer and the formation of a further layer or level of metal interconnects to be formed over the composite layer.

Thus, the formation of the barrier layer 20, the void-free first low k dielectric layer 24, and the second low k dielectric layer 30 can all be carried out in the multiple chambers of the same vacuum apparatus, resulting in improvements in both process economics as well as the quality of the processing.

While it is considered to be preferable to carry out all of the deposition steps to form the composite low k dielectric layer in a single vacuum apparatus, it is recognized that it may be desirable, in some applications, to eliminate any portions of the void-free layer on top of the metal lines so that vias subsequently formed down to the metal lines will not pass through any of the first (void-free) low k dielectric layer. Turning to Figures 6 and 7, this embodiment is illustrated. In Figure 6, the structure of Figure 3 is shown after a planarization step, such as a CMP step which removes portions 24c-24e of void-free first low k dielectric layer 24'

from above metal lines 14a-14c, leaving void-free portions 24a' and 24b'. Of course, this requires removal of the substrate from the vacuum deposition apparatus after the step of forming void-free first low k dielectric layer 24'. However, as shown in Figure 7, subsequent deposition of second low k dielectric layer 30', and formation of vias such as illustrated filled via 34' therethrough results in a via which does not pass through any portion of void-free dielectric layer 24'. No via poisoning attributable to exposure of layer 24', as a part of the sidewall of the via, can thus occur in this embodiment. Of course this embodiment, although requiring the planarizing step, still enjoys the advantage of the first embodiment of a more rapid deposition of the second layer of low k dielectric material, as compared to the deposition rate for the formation of the void-free low k dielectric material deposited in the first step when depositing void-free low k dielectric layer 24'.

The following will serve to further illustrate the invention.

Example

A semiconductor substrate can be provided having an oxide layer thereon with metal lines formed over the oxide layer to a metal line thickness (height) of 560 nm, (5.6 kÅ) and an average horizontal spacing between the metal lines of about 270 nm. The substrate, when placed in a first plasma CVD 5 liter vacuum deposition chamber, would be maintained therein at a pressure of ~350 mTorr and a temperature of 350°C. 150 sccm of silane gas, 3500 sccm of N₂O, and 1500 sccm of N₂ gases would be flowed into the chamber and a plasma can be ignited in the chamber at a power level of about 100 watts. The deposition may be continued for about 11 seconds until a conformal base layer of silicon oxide of about 500 Å in thickness is formed over the metal lines and the oxide layer.

The coated substrate can then be moved to a second 5 liter vacuum deposition chamber in the same vacuum apparatus (without exposing the substrate to the ambient atmosphere) where 70 sccm of methyl silane, 19 sccm of silane, and 0.75 grams/minute of hydrogen peroxide are flowed into the chamber, while the chamber is maintained at a pressure of 900 mTorr and a temperature of ~5°C. This deposition is carried out for ~40 seconds to fill the high aspect ratio

regions between the closely spaced apart metal lines with void-free low k carbon-doped silicon oxide dielectric material.

5 The substrate is then moved to a third vacuum chamber in the vacuum apparatus (again without exposing the coated substrate to ambient) where further low k silicon oxide dielectric material is deposited by PECVD over the previously deposited void-free low k carbon-doped silicon oxide dielectric material by flowing 150 sccm of tetramethyl silane and 500 sccm of O₂ into a 5 liter vacuum deposition chamber maintained at a pressure of 1000 mTorr and a temperature of ~ 17°C. A plasma is ignited in the chamber and maintained at a power of ~ 1000 watts during the deposition. This deposition may be carried out for 60 seconds to provide a second low k dielectric layer of about 1400 nm (14 kÅ).

10 The coated substrate can then be removed from the vacuum chamber, planarized by CMP, and vias may then be formed through the composite low k layer down to the metal lines. The substrate may then be examined for completeness of the via filling, i.e., to ascertain the amount of via poisoning. Substantially all of the vias will be found to be filled, indicating that the formation of the vias through the second layer of low k silicon oxide dielectric material, i.e., that the layer deposited by PECVD, does not contribute to via poisoning. Sectioning of the substrate followed by examination of the first low k silicon oxide dielectric layer using SEM should reveal the formation of a void-free low k dielectric material deposited in the high aspect ratio regions between the closely spaced apart metal lines.

15 20 Thus, the invention provides a composite layer of low k silicon oxide dielectric material wherein the portion of the composite low k layer of silicon oxide dielectric material deposited in the high aspect ratio regions between the closely spaced apart metal lines is void-free, while the second portion of the composite low k layer of silicon oxide dielectric material deposited above the first portion can be deposited at a much greater deposition rate, yet does not appear to contribute to poisoning of vias formed through the composite layer.

25 Having thus described the invention what is claimed is:

1. A process for forming a composite layer of low k silicon oxide dielectric material on an oxide layer of an integrated circuit structure on a semiconductor substrate having closely spaced apart metal lines thereon, said composite layer of low k silicon oxide dielectric material exhibiting void-free deposition properties in high aspect ratio regions between closely spaced apart metal lines, deposition rates in other regions comparable to standard k silicon oxide, and without exhibiting via poisoning characteristics, comprising the steps of:

- 5
- a) forming over said oxide layer and said metal lines a first layer of low k silicon oxide dielectric material exhibiting void-free deposition properties in high aspect ratio regions between said closely spaced apart metal lines, until said low k silicon oxide dielectric material reaches the level of the top of said metal lines on said oxide layer; and
- 10
- b) forming a second layer of low k silicon oxide dielectric material over said first layer at a higher deposition rate than said first layer.

2. The process of claim 1 wherein said steps to form said composite layer of low k silicon oxide dielectric material are all carried out in a single vacuum processing apparatus without removal of said semiconductor substrate from said vacuum apparatus.

3. The process of claim 2 wherein said second layer is deposited up to the desired overall thickness of the composite low k silicon oxide dielectric layer.

4. The process of claim 2 wherein said first layer of low k silicon oxide dielectric material exhibiting void-free deposition properties in high aspect ratio regions is formed by reacting a carbon-substituted silane with a mild oxidant.

5. The process of claim 4 wherein said mild oxidant comprises hydrogen peroxide.

6. The process of claim 4 wherein said carbon-substituted silane is selected from the group consisting of monomethyl silane, dimethyl silane, and trimethyl silane.

7 The process of claim 4 wherein said carbon-substituted silane comprises a carbon-substituted silane having only primary hydrogens bonded to the carbon atoms and having the formula: $\text{SiH}_x((\text{C})_y(\text{CH}_3)_z)_{(4-x)}$, where x ranges from 1 to 3, y is an integer from 1 to 4 for a branched alkyl group and from 3 to 5 for a cyclic alkyl group, and z is $2y+1$ for a branched alkyl group and $2y-1$ for a cyclic alkyl group.

8. The process of claim 2 wherein said first layer of low k silicon oxide dielectric material exhibiting void-free deposition properties in high aspect ratio regions is formed by reacting oxygen with either a carbon-substituted silane, a fluorine-substituted silane, or a mixture of same in a high density plasma.

9. The process of claim 2 wherein said second layer of low k silicon oxide dielectric material is formed over said first layer by reacting silane, O_2 , and one or more reactants selected from the group consisting of CH_4 , C_4F_8 , and SiF_4 in a PECVD process, whereby said second layer of low k silicon oxide dielectric material is deposited at a higher deposition rate than said first layer.

10. A process for forming a composite layer of low k carbon-doped silicon oxide dielectric material on an oxide layer of an integrated circuit structure on a semiconductor substrate, said composite layer of low k carbon-doped silicon oxide dielectric material exhibiting void-free deposition properties in high aspect ratio regions between closely spaced apart metal lines, deposition rates comparable to non carbon-doped silicon oxide, and without exhibiting via poisoning characteristics, comprising the steps of:

- 5
- 10
- 15
- a) forming over said oxide layer and said metal lines a first layer of low k carbon-doped silicon oxide dielectric material by reacting a carbon-substituted silane reactant with hydrogen peroxide until the resulting deposition of low k carbon-doped silicon oxide dielectric material reaction product reaches the level of the top of said metal lines on the oxide layer to form a low k silicon oxide dielectric material exhibiting void-free deposition properties in high aspect ratio regions between said closely spaced apart metal lines; and
 - b) forming a second layer of carbon-doped low k silicon oxide dielectric material over said first layer up to the desired overall thickness of the low k carbon-doped silicon oxide dielectric layer by plasma enhanced chemical vapor deposition (PECVD), whereby said second layer of low k silicon oxide dielectric material is deposited at a higher deposition rate than said first layer.

11. The process of claim 10 wherein steps to form said composite layer of low k silicon oxide dielectric material are all carried out in a single vacuum processing apparatus without removal of said semiconductor substrate from said vacuum apparatus.

12. The process of claim 11 wherein said second layer of low k silicon oxide dielectric material is formed over said first layer in said PECVD process, by reacting silane, O_2 , and one or more reactants selected from the group consisting of CH_4 , C_4F_8 , and SiF_4 .

13. The process of claim 1 wherein after said step of forming said first layer of low k silicon oxide dielectric material exhibiting void-free deposition properties in high aspect ratio regions between said closely spaced apart metal lines, said first layer is planarized prior to said step of forming said second layer of low k silicon oxide dielectric material.

14. The process of claim 13 wherein said step of planarizing said first layer of low k silicon oxide dielectric material further comprises a ~~chemical~~ mechanical polishing (CMP) step.

15. A composite layer of low k silicon oxide dielectric material on an oxide layer of an integrated circuit structure, said composite layer of low k silicon oxide dielectric material exhibiting void-free deposition properties in high aspect ratio regions, deposition rates in other regions comparable to standard k silicon oxide, and without exhibiting via poisoning characteristics, comprising:

- a) a first layer of low k silicon oxide dielectric material exhibiting void-free deposition properties in high aspect ratio regions, deposited until said low k silicon oxide dielectric material reaches the level of the top of metal lines on said oxide layer; and
- b) a second layer of low k silicon oxide dielectric material deposited over the first layer at a faster rate than the deposition rate of said first layer up to the desired overall thickness of the composite layer of low k carbon-doped silicon oxide dielectric material.

16. The composite layer of low k silicon oxide dielectric material of claim 15 wherein said first and second layers comprising said composite layer of low k silicon oxide dielectric material are all formed in a single vacuum processing apparatus without removal of said semiconductor substrate from said vacuum apparatus.

Add
AS

17. A composite layer of low k carbon-doped silicon oxide dielectric material on an oxide layer of an integrated circuit structure on a semiconductor substrate, said composite layer of low k carbon-doped silicon oxide dielectric material exhibiting void-free deposition properties in high aspect ratio regions, deposition rates comparable to non carbon-doped silicon oxide, and without exhibiting via poisoning characteristics, comprising:

- a) a first layer of low k carbon-doped silicon oxide dielectric material formed by reacting a carbon-substituted silane reactant with hydrogen peroxide until the resulting deposition of low k carbon-doped silicon oxide dielectric material reaction product reaches the level of the top of metal lines on the oxide layer; and
- b) a second layer of carbon-doped low k silicon oxide dielectric material formed over said first layer by plasma enhanced chemical vapor deposition (PECVD) up to the desired overall thickness of the low k carbon-doped silicon oxide dielectric layer.

Certification Under 37 CFR 1.10

I hereby certify that these documents referred to as enclosed herein are being deposited with the United States Postal Service on this date March 15, 2002 in an envelope as "Express Mail Post Office to Addressee" Mailing Label Number ET662218667US addressed to: Assistant Commissioner for, Washington, D.C. 20231.

John P. Taylor

Person Mailing Paper

John P. Taylor

Signature of Person Mailing Paper